

Package: rjdmarkdown (via r-universe)

September 17, 2024

Type Package

Title 'rmarkdown' Extension for Formatted 'RJDemetra' Outputs

Version 0.2.3

Description Functions to have nice 'rmarkdown' outputs of the seasonal and trading day adjustment models made with 'RJDemetra'.

SystemRequirements Java (>= 8)

Depends R (>= 3.1.1), RJDemetra

Imports knitr, kableExtra, magrittr

License EUPL

URL <https://github.com/AQLT/rjdmarkdown>

BugReports <https://github.com/AQLT/rjdmarkdown/issues>

Encoding UTF-8

RoxygenNote 7.2.3

VignetteBuilder knitr

Suggests rmarkdown, ggdemetra

Repository <https://aqlt.r-universe.dev>

RemoteUrl <https://github.com/AQLT/rjdmarkdown>

RemoteRef HEAD

RemoteSha 814398eed9b0867b70c4296ce5272edf00d4c0c9

Contents

create_rmd	2
print_decomposition	5
print_diagnostics	6
print_preprocessing	7
Index	9

`create_rmd`*Create and render 'rmarkdown' file*

Description

Function to create a 'rmarkdown' file with all the output and render it

Usage

```
create_rmd(  
  x,  
  output_file,  
  output_format = "pdf_document",  
  preprocessing_fun = print_preprocessing,  
  decomposition_fun = print_decomposition,  
  diagnostics_fun = print_diagnostics,  
  title = "Seasonal adjustment summary",  
  knitr_chunk_opts = list(fig.pos = "h", echo = FALSE, results = "asis", fig.cap =  
    "S-I Ratio"),  
  ...  
)  
  
## S3 method for class 'SA'  
create_rmd(  
  x,  
  output_file,  
  output_format = "pdf_document",  
  preprocessing_fun = print_preprocessing,  
  decomposition_fun = print_decomposition,  
  diagnostics_fun = print_diagnostics,  
  title = "Seasonal adjustment summary",  
  knitr_chunk_opts = list(fig.pos = "h", echo = FALSE, results = "asis", fig.cap =  
    "S-I Ratio"),  
  ...  
)  
  
## S3 method for class 'jSA'  
create_rmd(  
  x,  
  output_file,  
  output_format = "pdf_document",  
  preprocessing_fun = print_preprocessing,  
  decomposition_fun = print_decomposition,  
  diagnostics_fun = print_diagnostics,  
  title = "Seasonal adjustment summary",  
  knitr_chunk_opts = list(fig.pos = "h", echo = FALSE, results = "asis", fig.cap =  
    "S-I Ratio"),
```

```
    ...
  )

## S3 method for class 'workspace'
create_rmd(
  x,
  output_file,
  output_format = "pdf_document",
  preprocessing_fun = print_preprocessing,
  decomposition_fun = print_decomposition,
  diagnostics_fun = print_diagnostics,
  title = "Seasonal adjustment summary",
  knitr_chunk_opts = list(fig.pos = "h", echo = FALSE, results = "asis", fig.cap =
    "S-I Ratio"),
  ...
)

## S3 method for class 'multiprocessing'
create_rmd(
  x,
  output_file,
  output_format = "pdf_document",
  preprocessing_fun = print_preprocessing,
  decomposition_fun = print_decomposition,
  diagnostics_fun = print_diagnostics,
  title = "Seasonal adjustment summary",
  knitr_chunk_opts = list(fig.pos = "h", echo = FALSE, results = "asis", fig.cap =
    "S-I Ratio"),
  ...,
  workspace
)

## S3 method for class 'sa_item'
create_rmd(
  x,
  output_file,
  output_format = "pdf_document",
  preprocessing_fun = print_preprocessing,
  decomposition_fun = print_decomposition,
  diagnostics_fun = print_diagnostics,
  title = "Seasonal adjustment summary",
  knitr_chunk_opts = list(fig.pos = "h", echo = FALSE, results = "asis", fig.cap =
    "S-I Ratio"),
  ...,
  workspace
)
```



```
# To open the file:
browseURL(sub(".Rmd", ".pdf", output_file, fixed = TRUE))
browseURL(sub(".Rmd", ".html", output_file, fixed = TRUE))
```

print_decomposition *Print the decomposition*

Description

Function to print the decomposition model

Usage

```
print_decomposition(
  x,
  format = knitr::opts_knit$get("rmarkdown.pandoc.to"),
  plot = TRUE,
  digits = 3,
  decimal.mark = getOption("OutDec"),
  booktabs = TRUE,
  ...
)
```

Arguments

x	the object to print.
format	output format: "latex" or "html".
plot	boolean indicating whether to plot or not the S-I Ratio.
digits	number of digits after the decimal point.
decimal.mark	the character to be used to indicate the numeric decimal point.
booktabs	boolean indicating whether to use or not the booktabs package (when format = "latex").
...	arguments passed to plot.decomposition_X11 or plot.decomposition_SEATS .

Examples

```
ipi <- RJDemetra::ipi_c_eu[, "FR"]

jsa_x13 <- RJDemetra::jx13(ipi)
print_decomposition(jsa_x13, format = "latex")

sa_ts <- RJDemetra::jtramoseats(ipi)
print_decomposition(sa_ts, format = "html")
```

print_diagnostics *Print the diagnostics*

Description

Function to print diagnostics tests on the quality of the pre-processing and the decomposition

Usage

```
print_diagnostics(
  x,
  format = knitr::opts_knit$get("rmarkdown.pandoc.to"),
  signif.stars = TRUE,
  tests = c("mean", "skewness", "kurtosis", "ljung box",
    "ljung box (residuals at seasonal lags)", "ljung box (squared residuals)",
    "qs test on sa", "qs test on i", "f-test on sa (seasonal dummies)",
    "f-test on i (seasonal dummies)", "Residual seasonality (entire series)",
    "Residual seasonality (last 3 years)", "f-test on sa (td)", "f-test on i (td)"),
  digits = 3,
  decimal.mark = getOption("OutDec"),
  booktabs = TRUE,
  ...
)
```

Arguments

x	the object to print.
format	output format: "latex" or "html".
signif.stars	logical; if TRUE, p-values are additionally encoded visually as 'significance stars' in order to help scanning of long coefficient tables
tests	characters containing the names of the tests to print.
digits	number of digits after the decimal point.
decimal.mark	the character to be used to indicate the numeric decimal point.
booktabs	boolean indicating whether to use or not the booktabs package (when format = "latex").
...	unused arguments.

Examples

```
ipi <- RJDemetra::ipi_c_eu[, "FR"]

jsa_x13 <- RJDemetra::jx13(ipi)
print_diagnostics(jsa_x13, format = "latex")
```

```
sa_ts <- RJDemetra::tramoseats(ipi)
print_diagnostics(sa_ts, format = "html")
```

print_preprocessing *Print the pre-processing model*

Description

Function to print the pre-processing model

Usage

```
print_preprocessing(
  x,
  format = knitr::opts_knit$get("rmarkdown.pandoc.to"),
  signif.stars = TRUE,
  digits = 3,
  decimal.mark = getOption("OutDec"),
  booktabs = TRUE,
  summary = TRUE,
  likelihood = TRUE,
  arima = TRUE,
  regression = TRUE,
  ...
)
```

Arguments

x	the object to print.
format	output format: "latex" or "html".
signif.stars	logical; if TRUE, p-values are additionally encoded visually as 'significance stars' in order to help scanning of long coefficient tables
digits	number of digits after the decimal point.
decimal.mark	the character to be used to indicate the numeric decimal point.
booktabs	boolean indicating whether to use or not the booktabs package (when format = "latex").
summary	boolean indicating whether to use or not the summary section.
likelihood	boolean indicating whether to use or not the likelihood section.
arima	boolean indicating whether to use or not the arima section.
regression	boolean indicating whether to use or not the regression section.
...	unused.

Examples

```
ipi <- RJDemetra::ipi_c_eu[, "FR"]

sa_x13 <- RJDemetra::jx13(ipi)
print_preprocessing(sa_x13, format = "latex")

sa_ts <- RJDemetra::tramoseats(ipi)
print_preprocessing(sa_ts, format = "html")
```


Index

`create_rmd`, 2

`opts_chunk`, 4

`plot.decomposition_SEATS`, 5

`plot.decomposition_X11`, 5

`print_decomposition`, 4, 5

`print_diagnostics`, 4, 6

`print_preprocessing`, 4, 7

`render`, 4